

AUSTRALIA

SAFETY DATA SHEET

1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

1.1 Product identifier

Product name MOLYTEC CHROME COTE

Synonyms CHROME COTE • M878 • MOLYTEC CHROME-COTE

1.2 Uses and uses advised against

Uses AEROSOL DISPENSED • ENAMEL PAINT

1300 452 355

1.3 Details of the supplier of the product

MOLYTEC AUSTRALIA P/L
2/38-44 Enterprise Street, Cleveland, QLD, 4163, AUSTRALIA
1300 452 355
admin@molytec.com.au
http://www.molytec.com.au

1.4 Emergency telephone numbers

Emergency

2. HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

CLASSIFIED AS HAZARDOUS ACCORDING TO SAFE WORK AUSTRALIA CRITERIA

Physical Hazards

Aerosols - Flammable: Category 1 Aerosols - Pressurised: Category 1

Health Hazards

Serious Eye Damage / Eye Irritation: Category 2B Specific Target Organ Toxicity (Single Exposure): Category 3 (Narcotic Effects) Carcinogenicity: Category 1 Repeated exposure may cause skin dryness or cracking.

DANGER

Environmental Hazards

Aquatic Toxicity (Chronic): Category 2

2.2 GHS Label elements

Pictograms



Hazard statements

AUH066	Repeated exposure may cause skin dryness or cracking.
H222	Extremely flammable aerosol.
H229	Pressurized container: may burst if heated.
H320	Causes eye irritation.
H336	May cause drowsiness or dizziness.
H350	May cause cancer.
H411	Toxic to aquatic life with long lasting effects.

ChemAlert.

PRODUCT NAME MOLYTEC CHROME COTE

Prevention statements	
P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P264	Wash thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
Response statements	
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308 + P313 P391	IF exposed or concerned: Get medical advice/ attention. Collect spillage.
Storege statements	
Storage statements	
P403 + P233 P405	Store in a well-ventilated place. Keep container tightly closed. Store locked up.

Store locked up. P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C.

Disposal statements

Dispose of contents/container in accordance with relevant regulations.

2.3 Other hazards

P501

No information provided.

3. COMPOSITION/ INFORMATION ON INGREDIENTS

3.1 Substances / Mixtures

Ingredient	CAS Number	EC Number	Content
BUTANE, BRANCHED AND LINEAR	68513-65-5	271-009-7	20 to 40%
PROPANE	74-98-6	200-827-9	20 to 40%
MINERAL TURPENTINE	-	-	<30%
NAPHTHA, LOW BOILING POINT NAPHTHA	8030-30-6	232-443-2	<30%
ACETONE	67-64-1	200-662-2	<20%
ALKYD RESIN(S)	-	-	30 to 60%
PIGMENTS/EXTENDER(S)	-	-	<20%
ALUMINIUM FLAKE	-	-	<5%
DRIER(S)	-	-	<5%

4. FIRST AID MEASURES

4.1 Description of first aid measures

If in eyes, hold eyelids apart and flush continuously with running water. Continue flushing until advised to Eve stop by a Poisons Information Centre, a doctor, or for at least 15 minutes. Inhalation If inhaled, remove from contaminated area. To protect rescuer, use a Type A (Organic vapour) respirator or an Air-line respirator (in poorly ventilated areas). Apply artificial respiration if not breathing. If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running water. Skin Continue flushing with water until advised to stop by a Poisons Information Centre or a doctor. For advice, contact a Poisons Information Centre on 13 11 26 (Australia Wide) or a doctor (at once). If Ingestion swallowed, do not induce vomiting. Ingestion is considered unlikely due to product form. **First aid facilities** Eye wash facilities and normal washroom facilities should be available.

4.2 Most important symptoms and effects, both acute and delayed

See Section 11 for more detailed information on health effects and symptoms.



PRODUCT NAME MOLYTEC CHROME COTE

4.3 Immediate medical attention and special treatment needed

Treat symptomatically.

5. FIRE FIGHTING MEASURES

5.1 Extinguishing media

Dry agent, carbon dioxide or foam. Prevent contamination of drains and waterways.

5.2 Special hazards arising from the substance or mixture

Extremely flammable aerosol. May evolve toxic gases (carbon oxides, hydrocarbons) when heated to decomposition. Aerosol may explode at temperatures exceeding 50°C. Eliminate all ignition sources, including cigarettes, open flames, spark producing switches/tools, heaters, pilot lights, mobile phones, etc when handling. Aerosol cans may explode above 50°C.

5.3 Advice for firefighters

Evacuate area and contact emergency services. Toxic gases may be evolved in a fire situation. Remain upwind and notify those downwind of hazard. Wear full protective equipment including Self Contained Breathing Apparatus (SCBA) when combating fire. Use waterfog to cool intact containers and nearby storage areas.

5.4 Hazchem code

2YE

- 2 Fine Water Spray.
- Y Risk of violent reaction or explosion. Wear full fire kit and breathing apparatus. Contain spill and run-off.
- E Evacuation of people in and around the immediate vicinity of the incident should be considered.

6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Wear Personal Protective Equipment (PPE) as detailed in section 8 of the SDS. Clear area of all unprotected personnel. Ventilate area where possible.

6.2 Environmental precautions

Prevent product from entering drains and waterways.

6.3 Methods of cleaning up

Contain spillage, then cover / absorb spill with non-combustible absorbent material (vermiculite, sand, or similar), collect and place in suitable containers for disposal.

6.4 Reference to other sections

See Sections 8 and 13 for exposure controls and disposal.

7. HANDLING AND STORAGE

7.1 Precautions for safe handling

Before use carefully read the product label. Use of safe work practices are recommended to avoid eye or skin contact and inhalation. Observe good personal hygiene, including washing hands before eating. Prohibit eating, drinking and smoking in contaminated areas.

7.2 Conditions for safe storage, including any incompatibilities

Store in a cool (< 50°C), dry, well ventilated area, removed from incompatible substances, heat or ignition sources and foodstuffs. Ensure aerosol containers/ cans are adequately labelled, protected from physical damage and sealed when not in use. Check regularly for damaged/ leaking containers. Large storage areas should have appropriate fire protection systems.

7.3 Specific end uses

No information provided.



8. EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1 Control parameters

Exposure standards

Ingredient	Reference	TWA		STEL	
ingredient	Kelefence	ppm	mg/m³	ppm	mg/m³
Acetone	SWA [AUS]	500	1185	1000	2375
Acetone	SWA [Proposed]	250	594	1000	2375
Mineral Turpentine	SWA [AUS]		480		
Mineral turpentine	SWA [AUS]		480		
Propane	SWA [AUS]		Asph	yxiant	

Biological limits

Ingredient	Reference	Determinant	Sampling Time	BEI
ACETONE	ACGIH BEI	Acetone in urine	End of shift	25 mg/L

8.2 Exposure controls

Engineering controls Avoid inhalation. Use in well ventilated areas. Where an inhalation risk exists, mechanical explosion proof extraction ventilation is recommended. Flammable vapours may accumulate in poorly ventilated or confined areas. Vapours are heavier than air and may travel some distance to an ignition source and flash back.

PPE

Eye / Face	Wear splash-proof goggles.
Hands	Wear viton® or nitrile or neoprene gloves.
Body	When using large quantities or where heavy contamination is likely, wear coveralls.
Respiratory	At high vapour levels, wear a Type A-Class P1 (Organic gases/vapours and Particulate) respirator.
Body	When using large quantities or where heavy contamination is likely, wear coveralls.



9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

Appearance	SILVER LIQUID (AEROSOL DISPENSED)
Odour	SLIGHT ODOUR
Flammability	EXTREMELY FLAMMABLE
Flash point	-10°C (Propellant)
Boiling point	56°C (Acetone)
Melting point	NOT AVAILABLE
Evaporation rate	NOT AVAILABLE
pH	NOT AVAILABLE
Vapour density	NOT AVAILABLE
Relative density	0.95 to 1.0
Solubility (water)	INSOLUBLE
Vapour pressure	517 kPa @ 24°C
Upper explosion limit	9.6 % (Propellant)
Lower explosion limit	1.5 % (Propellant)
Partition coefficient	NOT AVAILABLE
Autoignition temperature	494°C to 600°C (Propellant)
Decomposition temperature	NOT AVAILABLE
Viscosity	NOT AVAILABLE
Explosive properties	NOT AVAILABLE
Oxidising properties	NOT AVAILABLE
Odour threshold	NOT AVAILABLE
9.2 Other information	
% Volatiles	70 % (Approximately)
	· · · · · · · · · · · · · · · · · · ·

ChemAlert.

10. STABILITY AND REACTIVITY

10.1 Reactivity

Carefully review all information provided in sections 10.2 to 10.6.

10.2 Chemical stability

Stable under recommended conditions of storage.

10.3 Possibility of hazardous reactions

Polymerization is not expected to occur.

10.4 Conditions to avoid

Avoid heat, sparks, open flames and other ignition sources.

10.5 Incompatible materials

Incompatible with oxidising agents (e.g. hypochlorites), acids (e.g. nitric acid), alkalis (e.g. sodium hydroxide), heat and ignition sources.

10.6 Hazardous decomposition products

May evolve toxic gases (carbon oxides, hydrocarbons) when heated to decomposition.

11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Acute toxicity

This product may have the potential to cause adverse health effects if intentionally misused (e.g. deliberately inhaling contents).

Information available for the ingredients:

Ingredient		Oral LD50	Dermal LD50	Inhalation LC50
PROPANE		Study not feasible	Study not feasible	> 800000 ppm/15M (rat)
NAPHTHA, LOW BO	DILING POINT NAPHTHA	> 5000 mg/kg (rat)	> 3000 mg/kg (rabbit)	
ACETONE		5800 mg/kg (rat)	> 7400 mg/kg (guinea pig, rabbit)	76000 mg/m³/4 hours (rat)
Skin	Contact may result in drying	g and defatting of the skin, ir	ritation, rash and dermatitis	
Eye	Contact may result in irritati	on, lacrimation, pain and rec	dness.	
Sensitisation	Not classified as causing sk	kin or respiratory sensitisatio	n.	
Mutagenicity	Not classified as a mutager	1.		
Carcinogenicity	May cause cancer.			
Reproductive	Not classified as a reproduc	ctive toxin.		
STOT - single exposure	Over exposure may result may result in nausea, dizzir		throat, coughing and head	dache. High level exposure
STOT - repeated exposure	Not classified as causing or	gan damage from repeated	exposure.	
Aspiration	Ingestion is considered unli the lungs may cause chemi			t is ingested, aspiration into

12. ECOLOGICAL INFORMATION

12.1 Toxicity

Toxic to aquatic life with long lasting effects.

12.2 Persistence and degradability

No information provided.

12.3 Bioaccumulative potential

No information provided.

12.4 Mobility in soil

No information provided.

ChemAlert.

PRODUCT NAME MOLYTEC CHROME COTE

12.5 Other adverse effects

Avoid contamination of drains and waterways.

13. DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Waste disposalFor small amounts, absorb contents with sand or similar and dispose of to an approved landfill site. Do not
puncture or incinerate aerosol cans. Contact the manufacturer/supplier for additional information (if required).LegislationDispose of in accordance with relevant local legislation.

14. TRANSPORT INFORMATION

CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE



	LAND TRANSPORT (ADG)	SEA TRANSPORT (IMDG / IMO)	AIR TRANSPORT (IATA / ICAO)
14.1 UN Number	1950	1950	1950
14.2 Proper Shipping Name	AEROSOLS	AEROSOLS	AEROSOLS
14.3 Transport hazard class	2.1	2.1	2.1
14.4 Packing Group	None allocated.	None allocated.	None allocated.

14.5 Environmental hazards

Marine Pollutant.

14.6 Special precautions for user

Hazchem code	2YE
GTEPG	2D1
EmS	F-D, S-U
Other information	The environmentally hazardous substance mark is not required when transported in packages of less than 5 kg/L (UN Model Regulations: Special Provision 375; IATA: Special Provision A197; IMDG: Special Provision 969) or less than 500 kg/L by Australian Road and Rail.

15. REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture				
Poison schedule	A poison schedule number has not been allocated to this product using the criteria in the Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP).			
Classifications	Safe Work Australia criteria is based on the Globally Harmonised System (GHS) of Classification and Labelling of Chemicals (GHS Revision 7).			
Inventory listings	AUSTRALIA: AIIC (Australian Inventory of Industrial Chemicals) All components are listed on AIIC, or are exempt.			

16. OTHER INFORMATION

Additional information AEROSOL CANS may explode at temperatures approaching 50°C.

RESPIRATORS: In general the use of respirators should be limited and engineering controls employed to avoid exposure. If respiratory equipment must be worn ensure correct respirator selection and training is undertaken. Remember that some respirators may be extremely uncomfortable when used for long periods. The use of air powered or air supplied respirators should be considered where prolonged or repeated use is necessary.



PRODUCT NAME MOLYTEC CHROME COTE

PERSONAL PROTECTIVE EQUIPMENT GUIDELINES:

The recommendation for protective equipment contained within this report is provided as a guide only. Factors such as form of product, method of application, working environment, quantity used, product concentration and the availability of engineering controls should be considered before final selection of personal protective equipment is made.

HEALTH EFFECTS FROM EXPOSURE:

It should be noted that the effects from exposure to this product will depend on several factors including: form of product; frequency and duration of use; quantity used; effectiveness of control measures; protective equipment used and method of application. Given that it is impractical to prepare a report which would encompass all possible scenarios, it is anticipated that users will assess the risks and apply control methods where appropriate.

Ab	bre	viati	ons

Abbreviations	ACGIH	American Conference of Governmental Industrial Hygienists		
	CAS #	Chemical Abstract Service number - used to uniquely identify chemical compounds		
	CNS	Central Nervous System		
	EC No.	EC No - European Community Number		
	EMS	Emergency Schedules (Emergency Procedures for Ships Carrying Dangerous		
		Goods)		
	GHS	Globally Harmonized System		
	GTEPG	Group Text Emergency Procedure Guide		
	IARC	International Agency for Research on Cancer		
	LC50	Lethal Concentration, 50% / Median Lethal Concentration		
	LD50	Lethal Dose, 50% / Median Lethal Dose		
	mg/m³	Milligrams per Cubic Metre		
	OEL	Occupational Exposure Limit		
	рН	relates to hydrogen ion concentration using a scale of 0 (high acidic) to 14 (highly alkaline).		
	ppm	Parts Per Million		
	STEL	Short-Term Exposure Limit		
	STOT-RE	Specific target organ toxicity (repeated exposure)		
	STOT-SE	Specific target organ toxicity (single exposure)		
	SUSMP	Standard for the Uniform Scheduling of Medicines and Poisons		
	SWA	Safe Work Australia		
	TLV	Threshold Limit Value		
	TWA	Time Weighted Average		
Report status	This document has been compiled by RMT on behalf of the manufacturer, importer or supplier of the product and serves as their Safety Data Sheet ('SDS').			
	It is based on information concerning the product which has been provided to RMT by the manufacturer, importer or supplier or obtained from third party sources and is believed to represent the current state of knowledge as to the appropriate safety and handling precautions for the product at the time of issue. Further clarification regarding any aspect of the product should be obtained directly from the manufacturer, importer or supplier.			
	While RMT has taken all due care to include accurate and up-to-date information in this SDS, it does not provide any warranty as to accuracy or completeness. As far as lawfully possible, RMT accepts no liability for any loss, injury or damage (including consequential loss) which may be suffered or incurred by any person as a consequence of their reliance on the information contained in this SDS.			
Prepared by	Risk Management Technologies 5 Ventnor Ave, West Perth Western Australia 6005 Phone: +61 8 9322 1711 Fax: +61 8 9322 1794 Email: info@rmt.com.au			

[End of SDS]

Web: www.rmtglobal.com